

FILTRE TRIPLE ACTION FILTROPURE® 5000

Ref : 5382036

FILTROPURE



The triple action FILTROPURE® 5000 assure a depth filtration, holding back 99,9% of particules up to 5 microns. This filter is suitable for both cold and hot water application.



1

Elimination of impurities, sand and sediments likely to damage equipments at the end of water circuit.



5000
8mm male

2

Decrease of chlorine rate and other bad taste and smell, potentially present in the water.



5000 N
1/4 thread

3

Significant decrease of scaling of heating equipments and limestone blocking.



5000 F
1/4 integrated quick connector

Technical Datas

Capacity	5000 L
Size	length : 31,5 cm [12,4"] diametre : 5,1 cm [2"]
Connectors	8 mm pipe socket [5/16"]
Medias	Activated carbon with granules - Scale inhibitor - Sediment filter
Usual operating flow rate	3 L/ min
Maximum operation pressure	8,0 bars
Minimum operating pressure	0,7 bar
Minimum water temperature	2°C
Maximum water temperature	38°C
Advised renewal frequency	6 months [Attention : after 6 months, filtration efficiency decrease and bacteriological risks increase.]

MISTRAL CONSTRUCTEUR

2 avenue Ambroise Croizat, 91130, Ris Orangis
Tel : +33 1 60 79 37 61 | Fax : +33 1 60 79 18 26
email : info@mistralcoolers.com | site : www.mistralcoolers.com

Normes et certifications

NSF Norme numéro 42
Réduction des particules : Class II (1-5 microns)
Réduction du chlore : Class I (>75%)

